

TEST CERTIFICATE

This is to certify that the nominated size and quality of the following SLR product has been inspected and tested with following results.



Page 1

Customer Sold To:
 HESNZ
 3 Heb Place
 Takamini, Auckland, New Zealand

Order:	4115	Test Standard:	EN1677
Invoice:	22191	Certificate No:	SLR19960
Material:	G80		
Date:	20/05/2018	Batch :	18-2
Brand	SLR	Colour:	Yellow

Item	Quantity (pcs)	Test Quantity (pcs)	Working Load Limit (ton) / WLL	Standard Breakage Force (ton) / BF	Fact Breakage Force (ton) / BF
SLR-54 EYE SCREW M10	150	3	1T	4T	4.03T, 4.07T, 4.05T
SLR-54 EYE SCREW M16	120	3	4T	16T	16.2T, 16.15T, 16.1T
SLR-54 EYE SCREW M20	120	3	6T	24T	24.3T, 24.17T, 24.2T
SLR-54 EYE SCREW M24	40	1	8T	32T	32.36T
SLR-54 EYE SCREW M30	10	1	12T	48T	48.17T
SLR-54 EYE SCREW M36	5	1	16T	64T	64.32T
SLR-54 EYE SCREW M42	8	1	24T	96T	96.28T
SLR-54 EYE SCREW M48	6	1	32T	128T	128.32T
SLR-55 EYE NUT M10	150	3	1T	4T	4.12T, 4.03T, 4.1T
SLR-55 EYE NUT M12	400	3	2T	8T	8.04T, 8.07T, 8.12T
SLR-55 EYE NUT M16	240	3	4T	16T	16.17T, 16.2T, 16.15T

Item	Quantity (pcs)	Test Quantity (pcs)	Working Load Limit (ton) / WLL	Standard Breakage Force (ton) / BF	Fact Breakage Force (ton) / BF
SLR-55 EYE NUT M20	150	3	6T	24T	24.32T, 24.17T, 24.2T
SLR-55 EYE NUT M24	75	2	8T	32T	32.18T, 32.3T
SLR-55 EYE NUT M30	30	1	12T	48T	48.26T
SLR-55 EYE NUT M36	8	1	16T	64T	64.15T
SLR-55 EYE NUT M48	4	1	32T	128T	128.3T

Item	Quantity (pcs)	Test Quantity (pcs)	Working Load Limit (ton) / WLL	Standard Breakage Force (ton) / BF	Fact Breakage Force (ton) / BF
SLR-303 LIFTING SCREW POINT M16X40	60	2	0°:2T 90°:1.12T	0°:8T 90°:4.48T	0°:8.07T 90°:4.58T
SLR-303 LIFTING SCREW POINT M16X100	30	1	0°:2T 90°:1.12T	0°:8T 90°:4.48T	0°:8.1T 90°:4.52T
SLR-303 LIFTING SCREW POINT M24X40	15	1	0°:6.3T 90°:3.15T	0°:25.2T 90°:12.6T	0°:25.32T 90°:12.67T
SLR-303 LIFTING SCREW POINT M36X50 8T	6	1	0°:11.8T 90°:8T	0°:47.2T 90°:32T	0°:47.36T 90°:32.1T
SLR-303 LIFTING SCREW POINT M48X50	4	1	0°:15T 90°:10T	0°:60T 90°:40T	0°:60.4T 90°:40.17T

Manufactured, Inspected and Tested for and on behalf of: