



Fabric: Polyester fibre

Green Pin® Shackle type	WLL shackle	dia-meter bow	width bow	WLL round sling	Material width round sling	Material thickness round sling	Proof loading (kN)
	t	a mm	b mm	t	c mm	d mm	kN
G-4161, G-4163	0.5	7	20	0.5	36	5	25
G-4161, G-4163	1	10	26	1	36	6	49
G-4161, G-4163	2	13.5	32	2	37	8	99
G-4161, G-4163	3.25	16	43	3	44	10	148
G-4161, G-4163	4.75	19	51	4	52	12	197
G-4161, G-4163	6.5	22	58	5	59	13	246
G-4161, G-4163	6.5	22	58	6	65	14	295
G-4161, G-4163	8.5	25	68	8	68	17	393
G-4161, G-4163	12	32	83	10	90	19	393
G-4161, G-4163	17	38	99	15	115	21	589
G-4161, G-4163	25	45	126	20	135	23	785
G-4161, G-4163	35	50	138	30	170	27	1178
G-4161, G-4163	42.5	57	160	40	190	37	1570
G-4163	85	75	190	60	190	75	2355
G-4163	85	75	190	80	230	86	3140
P-6036	120	95	238	100	260	96	3924

Fabric: High performance fibre

Green Pin® Shackle type	WLL shackle	dia-meter bow	width bow	WLL round sling	Material width round sling	Material thickness round sling	Proof loading (kN)
	t	a mm	b mm	t	c mm	d mm	kN
G-4161, G-4163	12	32	83	10	55	12	393
G-4161, G-4163	25	45	126	20	80	15	785
G-4161, G-4163	35	50	138	30	90	20	1178
G-4161, G-4163	42.5	57	160	40	110	24	1570
G-4161, G-4163	55	65	180	50	117	23	1962
G-4163	85	75	190	60	150	30	2355
G-4163	85	75	190	80	200	40	3140
P-6036	120	95	238	100	233	47	3924
P-6036	150	105	275	125	267	53	4905
P-6036	150	105	275	150	308	62	5886

• Note: WLL of the combination of Green Pin® shackle and roundsling is limited by the WLL of the round sling for all combinations.

